

Commercial Deutz Diesel Generator 40kVA BFM3T Engine Diesel Generator 50HZ 32kW

Basic Information

Place of Origin: CHINA
Brand Name: DELLENT
Certification: CE ISO
Model Number: DE-DD44

Minimum Order Quantity: 1*20GP CONTAINER
 Price: USD3000-4000
 Packaging Details: PLASTIC WRAP

• Delivery Time: 30 DAYS

Payment Terms: L/C, T/T, Western UnionSupply Ability: 500 PCS PER MONTH



Product Specification

Name: Commercial Deutz Diesel Generator

Cooling System: Water Cooling

Frequency: 50HZInsulation Class: H

• Noise Level: ≤75dB(A)

• Controller: Smartgen/Deepsea/ComAp

Phase: Three PhasePower: Diesel Generator

• Protection Grade: IP23

Prime Power: 32kW/40kVAStandby Power: 35.2kW/44kVA

• Highlight: Deutz Diesel Generator 40kVA,

Commercial Deutz Diesel Generator, Engine Diesel Generator 50HZ

Product Description

High Commercial Deutz 40kVA Generator , BFM3T Engine Diesel Generator ,

Light: CE Deutz 40kva Generator

.PRODUCT DESCRIPTION

CE Commercial 32kW Deutz 40kVA GeneratorBFM3T Engine Diesel Generator

Product Introduce:Deutz engine diesel generator we have all series from rated 20kva to 750kva.

Application fields:

Diesel generator are used in any situation where a reliable backup power source is necessary to maintain continuity of operations.
For example:
Healthcare, Data Centers, Telecommunications, Construction, Manufacturing, Oil and Gas, Military, Residential electricity.

Advantage of our Deutz diesel generator:

Deutz diesel generator have a sturdy housing Longer lifespan Lower maintenance costs Lower noise level Faster delivery time Better team service Higher level technical support.



Product parameters

Model	DE-DD44
Rated output (KW/KVA)	32kw
Rated voltage (V)	230/400V
Rated current(A)	57.8A
Rated frequency	50Hz
Power factor	0.8 lagging
Noise level dB(a)	70/1m
Excitation	Stamford Brushless self-excitation
Phase Number and connection	3-phase 4-wire system
Diesel Engine	UK,Germany diesel engine,4 stroke,water cooled
Alternator model	Stamford brushless self-excited, IP23,Class H.
Rated Power (kw/1500rpm)	32kw
Fuel consumption (g/kw*h)	≤238
Cylinder number	4 cylinders
Displacement (L)	3.3
Cooling system	Water cooling
	Altitude≤1000M, Cooling air temperature

Environmental Conditions		-15°C~ 40°C, Relative humidity≤90%
Start Method		12V Electric start
Dimension of set	L	2280
(mm)	W	900
	Н	1500
Net weight of set (kg)		1100
Other spare parts (1 piece)		Gallus Air filter element Diesel oil filter element
		Machinery oil Specification Special tool

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

ewest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:



















. FACTORY INTERIOR:



If you need Deutz generator with other models technical data, kindly contact us for catalogues!



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY,NINGDECITY,FUJIAN.CHINA